

1/9/1  
DIALOG(R) File 347:JAPIO  
(c) 2000 JPO & JAPIO. All rts. reserv.

02892321 \*\*Image available\*\*  
RESIST REMOVING APPARATUS

PUB. NO.: 01-189921 [JP 1189921 A]  
PUBLISHED: July 31, 1989 (19890731)  
INVENTOR(s): TAMURA KATSUHIKO  
APPLICANT(s): MITSUBISHI ELECTRIC CORP [000601] (A Japanese Company or Corporation), JP (Japan)  
APPL. NO.: 63-016127 [JP 8816127]  
FILED: January 26, 1988 (19880126)  
INTL CLASS: [4] H01L-021/30; G03C-011/00; G03F-007/00  
JAPIO CLASS: 42.2 (ELECTRONICS -- Solid State Components); 29.1 (PRECISION INSTRUMENTS -- Photography & Cinematography)  
JOURNAL: Section: E, Section No. 838, Vol. 13, No. 481, Pg. 127, October 31, 1989 (19891031)

#### ABSTRACT

PURPOSE: To prevent decrease of concentration of hydrogen peroxide solution and to enable resist to be removed stably, by dissolving ozone gas in a heated mixture of sulfuric acid and the hydrogen peroxide solution.

CONSTITUTION: Liquid mixture 2 consisting of concentrated sulfuric acid and hydrogen peroxide in proportions of about 4:1 is introduced into a chemical vessel 1 and heated by a heater 3 to a temperature of 100-130 deg.C. Then, ozone gas 4 is fed into the liquid from a bubbler 5. Bubbles of the ozone gas produced thereby are contacted with the heated liquid mixture 2 of the concentrated sulfuric acid and hydrogen peroxide, and a part of the ozone gas is dissolved in the solution. A wafer having resist thereon is dipped in the solution for about 15 minutes, whereby the resist is removed from the wafer. The resist removing solution may be substituted by a mixture of concentrated sulfuric acid and concentrated nitric acid. According to this method, deterioration of capability of removing the resist can be prevented effectively.

BEST AVAILABLE COPY